

Installing SIM cards - XAG Drones

[Support Article](#)

Install SIM Cards

- ARC3
 - Open SIM 1 Slot Cover
 - If an existing SIM is there, remove it
 - Insert SIM Contact side UP
- Drone
 - Remove 4 3mm mounting screws for Radar Bracket
 - Gently rest Radar Unit down
 - Remove 2 T6 Screws from SIM Card Cover
 - Install SIM Contact side DOWN in SIM slot 1 (in US Models SIM 2 is blank)
 - Reinstall SIM Card Cover
 - Reinstall Radar Mount Bracket
- [Video Guide](#)

QUESTIONS? Call (309) 361-7656



<https://support.hse-uav.com>

AMERICA'S SPRAY DRONE EXPERTS

Shop The Best Brands | Unbiased Advice | Application Services | Unmatched Support

HSE
HSE-UAV.COM

Installing SIM cards - XAG Drones

Configure APN Settings

- ARC3

- Power on ARC3, but **DO NOT** connect to ARC3 WiFi
- Open XAG APP > ME > Devices
- Tap 3 Dot Menu, tap “APN Configuration”
- Select Remote Controller
- Connect to ARC3 (Password 20070401)
- Enter Desired APN (AT&T: “broadband”), make sure there are no spaces before or after and press confirm
- Ensure “Configured” Prompt appears
- Restart RC and confirm Second LED is solid Green (2-3min)

QUESTIONS? Call (309) 361-7656



<https://support.hse-uav.com>

AMERICA'S SPRAY DRONE EXPERTS

Shop The Best Brands | Unbiased Advice | Application Services | Unmatched Support

HSE
HSE-UAV.COM

Installing SIM cards - XAG Drones

Configure APN Settings

- Drone

- Power on Drone
- Open XAG APP > ME > Devices
- Tap 3 Dot Menu, tap “APN Configuration”
- Select Drone
- Place drone in WiFi Mode as per APP instructions
 - Press FC button for 2-3s, release then press 2-3s, release.
Wait for orange LED
- Connect to Drone Wifi (Password 20070401)
- Enter Desired APN (AT&T: “broadband”), make sure there are no spaces before or after and press confirm
- Ensure “Configured” Prompt appears
- Cold restart drone (min 5m battery off)

QUESTIONS? Call (309) 361-7656



<https://support.hse-uav.com>

AMERICA'S SPRAY DRONE EXPERTS

Shop The Best Brands | Unbiased Advice | Application Services | Unmatched Support

HSE
HSE-UAV.COM